

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1-8. (Cancelled)

9. (Currently Amended) A door mirror for a vehicle, comprising:

a mirror housing having an open side and a swelled opposite side;

a positionable mirror mounted in the open side;

a light assembly mounted in the swelled opposite side, wherein the swelled opposite side has an opening for receiving the light assembly, the light assembly comprising:

an outer base;

an inner base incorporated into the outer base and provided with light sources; and

a lens portion abutted against the outer base from a side of the outer base where the inner base is incorporated into the outer base, wherein the lens portion and the outer base are integrated together by filling a resin material in a portion where the lens portion abuts against the outer base; and

a cover removably mounted to an upper portion of the swelled opposite side, wherein:

the light assembly is provided with a coupler that is capable of being connected to an external coupler in order to supply electric power to the light sources,

a base end portion of the coupler is accommodated into a first coupler supporting piece on an outer base side of the light assembly together with a lead wire connected to the light sources,

the first coupler supporting piece on the outer base side is abutted against a second coupler supporting piece on a lens portion side of the light assembly, and

the first coupler supporting piece and the second coupler supporting piece are integrated together by filling the resin material in a portion where the first coupler supporting piece abuts against the second coupler supporting piece in order to integrate the lens portion with the outer base.

10-20. (Cancelled)

21. (Currently Amended) ~~A door mirror equipped with a lamp body~~The door mirror according to claim 9, comprising wherein:

~~\_\_\_\_\_ a mirror portion and a lamp body mounted to a housing; and~~

~~\_\_\_\_\_ a cover covering the housing, wherein:~~

~~the mirror portion~~housing, the lamp body~~light assembly and the cover being are~~ separately formed;

~~the lamp body~~light assembly is incorporated into the mirror housing in a direction opposite to the ~~mirror portion~~; and

~~the lamp body~~light assembly is fixed to the mirror housing by abutting fixing portions incorporated into the mirror housing in a direction opposite to the mirror and protruding upward from the outer base against provided on the lamp body to mounting pieces provided on the mirror housing in the direction opposite to the mirror portion and tightening screws in the direction opposite to the mirror portion, with the fixing portions being covered by the cover that has been mounted to the mirror housing in the direction opposite to the mirror portion.

22. (New) The door mirror according to claim 21, wherein:

the second coupler supporting piece serves as an injection incoming port for injection molding of the lens portion, and

the second coupler supporting piece is formed in an upwardly protruding fashion and is covered by the cover that has been mounted to the housing in the direction opposite to the mirror portion.